

HK-IZE7IR03

700TVL Waterproof IR Camera



Model

HK-IZE7IR03: 700TVL, IR LED, IP66, NTSC, LENTE 3.6MM

Features

- > 1/3" SONY EXview HAD CCD II & Effio-E DSP
- > High resolution of 700TVL(Color)
- > Mini. Illumination of 0.02Lux@F1.2, 0Lux(IR On)
- > AGC, ATW, BLC
- > Lens: 3.6mm
- > Max IR distance is 20m
- > Dual-ring structure design adopted to prevent light leakage
- > IP66, DC12V

Specifications

Model	HK-IZE7IR03 PALM	HK-IZE7IR03 NTSC
Camera		
Image Sensor	1/3" EXview HAD CCD II	

HK-IZE7IR03

Video Format	HK-IZE7IR03 PALM	HK-IZE7IR03 NTSC
Effective Pixels	976(H) x582(V), 570K pixels	976(H) x 494(V), 480K pixels
Horizontal Resolution	Color: 700TVL	
Mini. Illumination	0.02Lux@F1.2	
Electronic Shutter	Auto: 1/50s~1/100,000s	Auto: 1/60s~1/100,000s
AGC	Auto	
White Balance	ATW	
Backlight	BLC	
Synchronization	Internal	
S/N Ratio	>60dB(AGC Off)	
Video Output	1Vp-p Composite Output (75Ω/BNC)	
Lens		
Focal Length	Default: 6mm (3.6mm, 8mm optional)	
Lens Type	Manual	
General		
Ingress Protection	IP 66	
IR Distance	Max. 20m	
Power Supply	DC12V±10%	
Power Consumption	Max 7W	
Working Temperature	-30°C~+60°C	
Dimension	82.7mm x 80.2mm x 153.5mm	
Weight	700g	

HK-IZE7IR03

Dimensions (mm)

