

# HK-IZD70003

---

## 700TVL Enhanced Mini Dome Camera



### Model

HK-IZD70003

### Features

- > 1/3" SONY EXview HAD CCD II & Effio-E DSP
- > High resolution of 700TVL(Color)
- > Mini. Illumination of 0.05Lux@F1.2
- > 2D- NR, AWB, AGC, BLC, HLC, ATR, MD, Privacy Masking, Picture Adjustment
- > Powerful OSD operational function
- > Lens: 3.6mm (2.8mm, 6mm, 8mm, 12mm optional)
- > Advanced tri-axis structure adopted and support 355° pan
- > DC12V

# HK-IZD70003

## Specifications

Model	PALM	HK-IZD70003
<b>Camera</b>		
Image Sensor	1/3" EXview HAD CCD II	
Video Format	PAL	NTSC
Effective Pixels	976(H) x 582(V), 570K pixels	976(H) x 494(V), 480BK pixels
Horizontal Resolution	Color: 700TVL	
Mini. Illumination	0.05Lux@F1.2	
Electronic Shutter	Auto: 1/50s~1/100,000s Manual: 1/50s, 1/120s, 1/250s, 1/500s, 1/1000s, 1/2000s, 1/4000s, 1/10,000s	Auto: 1/60s~1/100,000s Manual: 1/60s, 1/100s, 1/250s, 1/500s, 1/1000s, 1/2000s, 1/4000s, 1/10,000s
Synchronization	Internal	
S/N Ratio	>60dB	
Video Output	1Vp-p Composite Output (75Ω/BNC)	
<b>Lens</b>		
Focal Length	Default: 3.6mm (2.8mm, 6mm, 8mm, 12mm optional)	
Lens Type	Manual	
<b>Operational(OSD)</b>		
Lens	Manual /Auto	
Shutter / AGC	Auto / Manual	
White Balance	ATW / Push / User 1 / User 2 / ANTI CR / Manual / Push lock	
Backlight	Off / BLC / HLC	
Picture Adjustment	Mirror / Brightness / Contrast / Sharpness / Hue / Gain	
ATR	Off / On	
Motion Detection	Off / On (Sensitivity / Block display / Monitoring Area / Area selection)	
Privacy Masking	Off / On (Area selection / Color / Transparent / Mosaic)	
Day/Night	Auto / B/W / Color	
Noise Reduction	Off / 2D	
Camera ID	Off / On (Character / Position)	
Language	English, Chinese, French, German, Russian, Spanish, Portuguese, Japanese	
<b>General</b>		
Power Supply	DC12V±10%	
Power Consumption	Max 3W	
Working Temperature	-30℃~+60℃	
Dimension	Φ108.2mm x 86.3mm	
Weight	300g	

# HK-IZD70003

---

## Dimensions (mm)

