



Model NO.	HK-IZD8IRVF
VIDEO	
TV System	PAL/NTSC
Focal Length	2.8~12mm Manual VF Lens
Infrared LED	30 LEDs
IR Distance	25m
Infrared Spectrum	850nm
ENVIRONMENTAL	
Operation Temperature	-10°C~ +55°C
Storage Temperature	-20~ +60°C
Protection grade	Vandal proof
ELECTRICAL	
Maximum power	4W
Adapter Requirement	DC12V 1A

HK-IZD8IRVF



MECHANICAL	
Color	White
Bracket	/
Net Weight	777g
Image Device	1/3" Super HAD CCD II
Effective Pixels	976(H)x582(V)@PAL 976(H)x494(V)@NTSC
Scanning System	2:1 Interlace
Synchronization	Internal
Horizontal Resolution	850TVL
S/N Ratio	>48dB (AGC closed)
Video Output	1Vp-p,75ohm, BNC
Min. Illumination	0.03 Lux(F1.2,5600°K)/0 Lux(IR on)
Language	8 kinds(Chinese English Japanese Spanish Portuguese Russian German French)
Scene Select	custom/FullAuto/INDOOR/OUTDOOR/BACKLIGHT/ITS
shutter/agc	Auto/Manual/fix
Shutter	256-1/10000
AE Level	0-100
AGC Max	6,12,16,24,30,36,42,44.8
Sens up	Auto/Off
white bal	ATW/PUSH/Manual/PUSH Lock
HLC/BLC	HLC/BLC/OFF
ATR-EX	Contrast/Clear Face
DNR	0-6
DAY/NIGHT	Auto/Day/Night
IR Optimizer	OFF/ON
LENS SHD COMP	ON/OFF

DEFOG	ON/OFF
FLK LESS	AUTO/ON/OFF
ANTI CR	AUTO/ON/OFF
PICT ADJUST	BRIGHTNESS/CONTRAST/SHAPPNESS/HUE/COLOR GAIN
EZOOM	1-255
DIS	ON/OFF
PRIVACY MASK	1\15
MOTION DET	1\4
LENS	MANNUAL/AUTO
FLIP	OFF/V/H/HV
LCD\CRT	CRTLCD
LANGUAGE	8 kinds(Chinese English Japanese Spanish Portuguese Russian German French)
MAINTENANCE	CAMERA RESET