

HK-IZDIPMWP

1.3Megapixel IR Network Dome Camera



Features

- 1/3" 1.3Megapixel progressive scan Aptina CMOS
- H.264 & MJPEG dual-stream encoding
- Max 15fps@1.3M(1280×960)&25/30fps@720P(1280×720)
- Day/Night(ICR), 2DNR, Auto iris, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 2.8~12mm varifocal lens
- Built-in 1/1 alarm in/out
- Max IR LEDs length 20m
- Micro SD memory, PoE

HK-IZDIPMWP

Technical Specifications

Model		HK-IZDIPMWP	
Camera			
Image Sensor	1/3" 1.3Megapixel Aptina CMOS		
Effective Pixels	1280(H)x960(V)		
Scanning System	Progressive		
Electronic Shutter Speed	Auto/Manual 1/4~1/10000		
Min. Illumination	0.1lux/F1.4(color),0.005Lux/F1.4(B/W),0Lux(IR on)		
S/N Ratio	>50dB		
Camera Features			
Max. IR LEDs Length	20m		
Day/Night	Auto(ICR)/Color/B/W		
Backlight Compensation	Off/BLC/HLC/DWDR		
White Balance	AUTO		
Gain Control	Auto/Manual		
Noise Reduction	2D		
Privacy Masking	Up to 4 areas		
Lens			
Focal Length	2.8~12mm		
Max Aperture	F1.4		
Focus Control	Manual		
Angle of View	H: 92°(Wide)~27.2°(Tele)		
Lens Type	Manual/Auto Iris (DC)		
Mount Type	Board-in Type		
Video			
Compression	H.264 / MJPEG		
Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×480) / CIF(352×240) /		
Frame Rate	Main Stream	1.3M(1 ~ 15fps)/720P(1 ~ 25/30fps)	
	Sub Stream	D1/CIF(1 ~ 25/30fps)	
Bit Rate	H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 12288Kbps		
Audio			
Compression	G.711a / G.711u (64kbps)/ PCM(128kbps)		
Interface	1/1 channel In/Out		
Network			
Ethernet	RJ-45 (10/100Base-T)		
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour		

HK-IZDIPMWP

ONVIF	ONVIF Ver. 2.0
Max. User Access	10 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Auxiliary Interface	
Memory Slot	Micro SD, Max 32GB
Alarm	1/1 channel In/Out
General	
Power Supply	DC12V, PoE(802.3af)
Power Consumption	<6W
Working Environment	-10°C~+60°C, 10%~90%
Dimensions	Φ140.3x113.7mm
Weight	0.8kg

Dimensions (mm)

