

## HKIZCONSHD

### HD Network Control Keyboard



**HKIZCONSHD:** Programmable 4D-switch desktop HD Network keyboard

### Features

- > Keyboard to Control:
  - ITZUMI Standalone DVR
  - ITZUMI (Network) High Speed Dome
  - ITZUMI High Speed Dome
  - Central Management Platform
  - Network Video Server
- > RS232, RS485 & Network Connections
- > Four Dimensional Joystick Control of PTZ Functions
- > Support full HD 1080p live view; Support HDMI & VGA sync output
- > Support snapshot and recording to U-disk
- > Support Video-Wall display
- > Support external Wi-Fi (Optional)
- > Support bidirectional talk
- > Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control
- > Auxiliary Functions, OSD and operation guides.

## Technical Specifications

<b>Model</b>	<b>HKIZCONSHD</b>		
<b>System</b>			
Main Processor	Industrial embedded microprocessor		
Operation System	Embedded LINUX		
<b>Audio</b>			
Compression	G.711A		
Output	1ch output		
Bidirectional Talk	1ch input and 1ch output		
<b>Display</b>			
Display split	1/4/8/9/16		
Resolution	1080P/720P/D1/HD1/BCIF/CIF/QCIF		
Screen	10.2" touch screen LCD (touch pen)		
<b>General</b>			
Keyboard Panel	Electromechanical		
Joystick	4-axis(zoom, focus, iris)		
Control	Output Control	Support video-wall display HDMI/VGA output	
	Control Mode	Direct Mode	Interface: 1 RS232/ 2 RS485 DVR Protocol: DH1/DH2 Dome Protocol: DH-SD/PELCO-D/PELCO-P/PELCO-D1/PELCO-P1 and etc.
		Network Mode	Interface: RJ45(1 RJ-45 port (10/100/1000M)) / Wi-Fi DVR/Network Dome: IP Address/Port/Protocol
Max Remote Users	20 (each can manage up to 256 unit devices)		
USB Interface	2 ports, for mouse control & backup		
<b>Environmental</b>			
Power Supply	DC12V		
Power Consumption	5W		
Working Temperature	-10℃ ~+55℃		
Working Humidity	10%~90%		
Atmosphere Pressure	86kpa~106kpa		
Dimension	480mmx240mmx87mm (WxDxH) (height: exclude joystick)		
Weight	4.5KG		