

HK-IZD7IR03

700TVL Waterproof IR Dome Camera



Model

HK-IZD7IR03: 700TVL, IR LED, IP66, NTSC

Features

- > 1/3" SONY EXview HAD CCD II & Effio-E DSP
- > High resolution of 700TVL(Color)
- > Mini. Illumination of 0.02Lux@F1.2, 0Lux(IR On)
- > AGC, ATW, BLC
- > Lens: 3.6mm (2.8mm, 6mm, 8mm, 12mm, 16mm optional)
- > Max. IR distance is 20m
- > IP66, DC12V

HK-IZD7IR03

Specifications

Model	PALM	HK-IZD7IR03
Camera		
Image Sensor	1/3" EXview HAD CCD II	
Video Format	PAL	NTSC
Effective Pixels	976(H) x 582(V), 570K pixels	976(H) x 494(V), 480K pixels
Horizontal Resolution	Color: 700TVL	
Mini. Illumination	0.02Lux@F1.2 (0Lux IR LED On)	
Electronic Shutter	Auto: 1/50s~1/100,000s	Auto: 1/60s~1/100,000s
AGC	Auto	
Day/Night	Auto / B/W/ Color	
White Balance	ATW	
Backlight	BLC	
Synchronization	Internal	
S/N Ratio	>50dB	
Video Output	1Vp-p Composite Output (75Ω/BNC)	
Lens		
Focal Length	3.6mm (2.8mm, 6mm, 8mm, 12mm, 16mm optional)	
Lens Type	Manual	
General		
Ingress Protection	IP 66	
IR Distance	Max. 20m	
Power Supply	DC12V±10%	
Power Consumption	Max 6W	
Working Temperature	-30°C~+60°C	
Dimension	Φ135mm x 104.5mm	
Weight	600g	

HK-IZD71R03

Dimensions (mm)

