

HK-IZ0232D1

32 Channel 2CIF 1.5U Standalone DVR



Features

- > Up to 32 cameras with 1080p realtime preview
- > H.264 dual-stream video compression
- > Full channel 2CIF or every 4ch: 1ch D1 & 3ch CIF realtime recording
- > HDMI / VGA / TV / Spot simultaneous video output
- > All channel simultaneous realtime playback, GRID interface & smart search
- > 3D intelligent positioning with Itzumi PTZ dome camera
- > Support 2 SATA HDDs up to 8TB, 2 USB2.0
- > Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

HK-IZ0232D1

Technical Specifications

Model	HK-IZ0232D1	
System		
Main Processor	Dual-core embedded processor	
Operating System	Embedded LINUX	
Video		
Input	32 channel, BNC	
Standard	NTSC(525Line, 60f/s), PAL(625Line, 50f/s)	
Audio		
Input	4 channel, BNC	
Output	1 channel, BNC	
Two-way Talk	1 channel Input 1 channel Output(Reuse the audio output channel), BNC	
Display		
Interface	1 HDMI, 1 VGA, 1 TV, 1 Spot, BNC	
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768	
Display Split	1/4/8/9/16/25/36	
Privacy Masking	4 rectangular zones (each camera)	
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording	
Recording		
Video/Audio Compression	H.264 / G.711	
Resolution	D1/4CIF(704×576/704×480) / HD1(352×576/352×480) / 2CIF(704×288/704×240) / CIF(352×288/352×240) / QCIF(176×144/176×120)	
Record Rate	Main Stream:	2CIF/CIF(1~25/30fps), D1 / HD1 (1~12/15fps),
	Extra Stream	CIF/QCIF(1~25/30fps)
Bit Rate	48~2048Kb/s	
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop	
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec	
Video Detection & Alarm		
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen tips	
Video Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank	
Alarm Input	16 channel	

Relay Output	3 channel
Playback & Backup	
Sync Playback	1/4/9/16/25/36
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search

HK-IZ0232D1

Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / Network / Internal SATA burner
Network	
Ethernet	RJ-45 port (10/100M/1000M)
Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, Alarm Server
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Storage	
Internal HDD	2 SATA ports (2HDDs or 1HDDs+1CD/DVD-RW), up to 8TB
Auxiliary Interface	
USB Interface	2 ports (1 Rear), USB2.0
RS232	1 port, For PC communication & Keyboard
RS485	1 port, For PTZ control
General	
Power Supply	DC 12V/ 5A
Power Consumption	25W(without HDD)
Working Environment	-10 ~+55°C / 10~90%RH / 86~106kpa
Dimension(W×D×H)	1.5U, 325mm×240mm×45mm
Weight	5.0KG(without HDD)

System Connection



